

PROCHEM

Your Source for Local Supply and Support

INSTRUMENTATION TOOLING AND ACCESSORIES



PIPING PRODUCTS



INSTRUMENTATION



VALVES AND ACTUATORS



MANUFACTURING



INDENT SERVICE



HYDRAULIC



A **REN** COMPANY

TOOLING



For absolute reliability and seamless installation, contact Prochem for your tooling needs.

Prochem Installation and Safety Training improves the overall safety of your fluid system installations to ensure installation integrity and reliability.

Train your staff with Prochem!!



RIDGID® 600 SERIES Lever Benders



The RIDGID® 600 Series Lever Benders are designed to easily bend materials such as copper, steel, stainless steel and other hard metal tube to a maximum of 180°. Built-in rollers and a heavy-duty handle design combine to produce high quality bends with greatly reduced effort when compared to conventional benders.


Part Number	Tube OD	Bend Radius
38028	3/16"	5/8"
38033	1/4"	5/8"
38038	5/16"	15/16"
38043	3/8"	15/16"
38048	1/2"	1-1/2"
38053	6 mm	16 mm
38038	8 mm	24 mm
38058	10 mm	24 mm
38063	12 mm	38 mm

The benders can be used either hand held or with the bender mounted in a vice. Vice mounting is especially useful when bending hard or thick walled materials.

The benders have inbuilt features allowing users to make 180° bends without removing the tube or the handles from the bender. Further, you do not have to cross the handles to make the 180° bend. This is unlike other benders where removal of the tube or handles and crossing of the handles is common meaning the **RIGID 600 Series Lever Benders** are by far the easiest to use.

The instructions are shown below.

1. Once the tube has been bent 90°, turn the carriage handle so that the pin moves to the “unlock” position.
2. Rotate the handle around the carriage until the 90-180° triangle mark on the handle aligns with the triangle mark on the carriage.
3. Turn the carriage handle so that the pin moves toward the “lock” position. Make sure the handle is secure to the carriage.
4. Continue to bend the tube to the desired angle up to 180°. The handles will not cross.





35S STAINLESS STEEL TUBING CUTTER

The 35S has been designed for optimised performance on Stainless Steel Tube.

Features:

- Six individual bearings replace traditional rollers. The bearings create a smoother cut, and allow for increased speed around the tube.
- A contoured frame allows for easy alignment while adjusting the cutter to make the cut.
- Specially designed Stainless Steel cutter wheel contains bearings in the hub, to decrease drag around the tube for a smoother cut.
- Ergonomic knob allows for easy adjustments.

Part Number	Model Number	Description	Tube OD	
			mm	inch
29963	35S	Stainless Steel Tubing Cutter with Cutter Wheel	6 to 35	1/4 to 1-3/8
29973	E635	Replacement Stainless Steel Cutter Wheel		



223S/227S INNER-OUTER REAMERS

Features:

- Integrated measurement tool allows you to easily measure pipe size.
- 227S features 45 cutting edges on the Inner and Outer cone allowing for fast, clean Inner reaming and Outer deburring. The 223S features 36 cutting edges.

Part Number	Model Number	Description	Tube OD	
			mm	inch
29983	223S	Inner-Outer Reamer	9 to 32	3/8" to 1-1/4"
29993	227S	Inner-Outer Reamer	12 to 51	1/2" to 2"



127S INNER-OUTER REAMERS

Specifically manufactured for Prochem, the blades have been designed to enable easy and more efficient deburring of 6.3 mm (1/4") OD tubing.

Capable of use on tubing up to 38 mm (1-1/2") OD.

Part Number	Model Number	Description	Tube OD	
			mm	inch
43573	127S	Inner-Outer Reamer	6 to 38	1/4" to 1-1/2"

RATCHET TUBE WRENCHES

Models R9 – R14

Features:

- Made from a high-quality carbon and stainless steel, RIDGID Ratchet.
- Tube Wrenches can be used in a wide variety of applications from plumbing to hydraulics.
- The spring-loaded jaws snap open and close around the fitting, enabling the tool to be used in tight quarters.
- The multi-point contact of the wrench helps prevent distortion of thin-walled fittings.



Part Number	Model Number	Description	Capacity	GYROLOK® Nut
48552	R9	Ratcheting Tube Wrench	9/16"	1/4"
48562	R11	Ratcheting Tube Wrench	11/16"	3/8"
48577	R14	Ratcheting Tube Wrench	7/8"	1/2"

GYROGAGE – GG

A calibrated instrument designed to give installer and inspector absolute confidence that a fitting has been made-up properly.



Features	Benefits
Missing ferrule indicator:	Maximises system safety by confirming that all components are in place.
Scribing tool:	Assures proper assembly by marking tubing to show that it has been properly inserted into fitting, and that fitting has been properly tightened.
Usable by both assembler and post assembly inspector:	Redundant method of verification.
Color-coded gauges:	Simplifies selection of appropriate system gauge: metric (blue) or fractional (green).
Size markings:	Simplifies selection of appropriate size gauge.
Single tool per size:	Eliminates need for extra tools; use one tool for installation and inspection, even for hard-to-reach assemblies.
Choice of marking methods:	Adds flexibility to assembly and inspection with choice of marking systems: built-in scriber or separate ink marker*.



Part Number	Tube Size		Replacement Scribes*
	mm	inch	
Fractional Sizes			
1GG	1.58	1/16	SPGGK1
2GG	3.18	1/8	SPGGK2
3GG	4.76	3/16	SPGGK3
4GG	6.35	1/4	SPGGK4
6GG	9.53	3/8	SPGGK4
8GG	12.70	1/2	SPGGK4
10GG	15.88	5/8	SPGGK5
12GG	19.05	3/4	SPGGK5
14GG	22.23	7/8	SPGGK5
16GG	25.40	1	SPGGK5

Part Number	Tube Size		Replacement Scribes*
	mm		
Metric Sizes			
3GG/MM	3		SPGGK2
6GG/MM	6		SPGGK4
8GG/MM	8		SPGGK4
10GG/MM	10		SPGGK4
12GG/MM	12		SPGGK4
14GG/MM	14		SPGGK5
16GG/MM	16		SPGGK5
18GG/MM	18		SPGGK5
20GG/MM	20		SPGGK5
22GG/MM	22		SPGGK5
25GG/MM	25		SPGGK5

* GYROGAGE scribes can be quickly and easily replaced using the referenced kit numbers.

GYROLOK[®] Marking Tool – GMT

The GYROLOK[®] Marking Tool provides the installer with an economical means of ensuring both proper tubing insertion into the fitting and adequate nut tightening.

Part Number	Size
2GMT	1/8"
4GMT	1/4"
6GMT	3/8"
8GMT	1/2"
10GMT	5/8"
12GMT	3/4"
16GMT	1"
468GMT	1/4" + 3/8" + 1/2"



Hydraulic Pre-setting Tool – HPST

Larger tube fittings often require more effort to assemble properly than can be consistently achieved using hand wrenches. HOKE® offers a portable Hydraulic Pre-setting Tool to make the assembly of larger fittings:

- Safer. The Hydraulic Pre-setting Tool helps assure consistently correct assembly of larger fittings.
- Simpler. Interchangeable die sets allow easy conversion from one tube and fitting size to another.
- More cost-efficient. Using the Hydraulic Pre-setting Tool extends fitting life and reduces assembly time.



Using the portable Hydraulic Pre-setting Tool, the GYROLOK® nut and ferrule system is initially set onto the tubing. The pre-set fitting and tube assembly is then easily installed by following the GYROLOK® reassembly instructions.

How it works

GYROLOK® nut and ferrule system components are assembled onto Hydraulic Pre-Setting Tool. Hand pump is operated until indicator arm releases.

Pre-set tube assembly is ready for installation using standard GYROLOK® remake instructions.

Features	Benefits
One basic pre-setting head for all sizes:	Provides versatility and value by covering sizes from 1/2" through 2" and 12 mm through 50 mm.
Interchangeable die sets:	Allows easy conversion from one tube and fitting size to another.
10,000 psi hydraulic pump:	Provides the force necessary for consistent, fast, and simple fitting assembly.
Carrying case:	Rugged steel carrying case offers easy transportation as well as a single storage location for all tool components.

Pre-setting Tool – PST

Where limited space prevents easy tightening of the fitting nut, the PST can be used pre-swage the ferrules to the tubing to ensure correct tightening and ultimately a well made-up fitting.







Part Number	Tube OD	Dimensions — inches	
		Length	Across Flats
1PST	1/16	2.25	3/8
2PST	1/8	1.94	11/16
3PST	3/16	2	1/2
4PST	1/4	1.94	11/16
6PST	3/8	1.97	11/16
8PST	1/2	2	7/8
12PST	3/4	2.50	1 1/8
16PST	1	2.50	1 1/2

Part Number	Tube OD	Dimensions — mm	
		Length	Across Flats
3PSTMM	3	49.2	17.3
6PSTMM	6	49.0	17.3
8PSTMM	8	50.0	17.3
10PSTMM	10	50.8	17.3
12PSTMM	12	50.8	22.0
14PSTMM	14	50.8	22.0
16PSTMM	16	63.5	28.4
18PSTMM	18	63.5	28.4
20PSTMM	20	63.5	28.4
22PSTMM	22	63.5	37.9
25PSTMM	25	63.5	37.9



STAINLESS STEEL
FLANGES
FITTINGS
PIPE
TUBE
VALVES
PYPLOK
FITTINGS
TWT
TUBE-MAG
PIPING TECHNOLOGIES

GYROLOK[®]
 **CIRCLE SEAL CONTROLS**
HOKE
GO REGULATOR
 **ANDERSON GREENWOOD**
INSTRUMENT TUBE
Classic FILTERS
CIRCOR
INSTRUMENTATION TECHNOLOGIES
 **BuTech**
MILTON ROY
KING

 **AMPO**
POYAM VALVES
 **BSM**[®]
ATC
ACTUATOR TECHNOLOGY COMPANY
PACSON valves
 **ANDERSON GREENWOOD**
 **HABONIM**
Industrial Valves & Actuators



A **pen** company

FOR FURTHER DETAILS PLEASE CONTACT YOUR LOCAL PROCHEM OFFICE

ADELAIDE

3A CB Fisher Drive, CAVAN
South Australia
Australia 5094
Telephone 61-8-8241 7633
Facsimile 61-8-8241 7644
Email sales@prochem.com.au

HOBART

96-98 Central Avenue
Derwent Park, Tasmania
Australia 7009
Telephone 61-3-6272 8828
Facsimile 61-3-6272 8688
Email sales@prochem.com.au

PERTH

6 Forge Street
Welshpool, Western Australia
Australia 6106
Telephone 61-8-9458 7777
Facsimile 61-8-9351 8170
Email sales@prochem.com.au

NEW ZEALAND

560 Arthur Porter Drive
Te Rapa Gateway
Hamilton, Waikato, 3200
Telephone 64-7-444 5458
Email nzlsales@prochemgroup.co.nz

BRISBANE

1-5 Kingsbury Street
Brendale, Queensland
Australia 4500
Telephone 61-7-3265 2711
Facsimile 61-7-3265 7430
Email sales@prochem.com.au

MELBOURNE

5-15 Ventura Place
Dandenong South, Victoria
Australia 3175
Telephone 61-3-9799 2244
Facsimile 61-3-9799 2255
Email sales@prochem.com.au

SYDNEY

30 Enterprise Circuit
Prestons, New South Wales
Australia 2170
Telephone 61-2-9727 0044
Facsimile 61-2-9728 6766
Email sales@prochem.com.au

www.prochem.com.au | [1300 287 777](tel:1300287777) | sales@prochem.com.au